

## Gyprock™ Ceiling Solutions

DATA SHEET

### Range Overview

Gyprock™ ceiling tiles have a plasterboard core and are used as decorative linings in commercial applications. They are square edged to suit an exposed grid and have various surface finishes. Offering an attractive, economical and functional solution for commercial and industrial ceilings, Gyprock™ ceiling systems are used in offices, shops and shopping centers, clubs, restaurants, function centers and community buildings, warehouse and factory buildings. The range of Gyprock™ ceiling tile systems suits both decorative and acoustic requirements.



#### Gyprock Freshtone™ Diamond White

Freshtone™ is a Gyprock™ plasterboard panel finished with a finely textured vinyl laminate which resists fading and mould growth. Gyprock Freshtone™ is available in 'white', and is ideal for shopping centres, offices and industrial premises. Freshtone's core features the sag resistance properties of Supaceil™.



#### Gyprock Supatone™

Gyprock Supatone™ is a plasterboard panel with a 'wipe clean' smooth polycoated surface paper laminate. Supatone™ is available in 'white', and used in basic commercial ceiling applications. Supatone's core features the sag resistance properties of Supaceil™.



#### Gyprock™ Perforated Panel

Gyprock™ Perforated Panels have been specifically developed for use in ceilings where additional sound absorption is required. Perforations are approximately 10% of the panel area, and combined with suitable insulation, provide a medium level of acoustic absorption.



## DATA SHEET



### Gyprock Freshtone™ Diamond White

Freshtone™ Diamond White has a lightly textured vinyl surface suitable for shopping centres, factories and offices.



### Gyprock Supatone™

Supatone™ ceiling tiles have a smooth polycoated surface white paper laminate, suited to basic commercial ceilings.



### Gyprock™ Perforated Panel

Perforated Panel has a white vinyl face finish, and a regular grid of 6mm full depth holes.

PRODUCT	FRESHTONE™ DIAMOND WHITE
Thickness	10mm
Surface Finish visible	Vinyl laminate
Surface Finish back	Paper
Core	Plaster
Edge Profile	Square
Edge Finish	Short edges paper wrapped, long edges machine cut
Grid	To suit an exposed grid
Accessibility	Easily demountable
Cleaning	Dust, vacuum or wipe with a damp cloth
Panel Mass (kg/m <sup>2</sup> )	7
Colour	White
EFHI	0, 0, 0, 3
CAC	35dB
Availability	Stock
Size	Nominal 1200 x 600mm Actual 1191 x 591mm
Pallet Size	200 Tiles

PRODUCT	SUPATONE™
Thickness	10mm
Surface Finish visible	Paper
Surface Finish back	Paper
Core	Plaster
Edge Profile	Square
Edge Finish	Short edges paper wrapped, long edges machine cut
Grid	To suit an exposed grid
Accessibility	Easily demountable
Cleaning	Dust, vacuum or wipe with a damp cloth
Panel Mass (kg/m <sup>2</sup> )	8
Colour	White
EFHI	13, 0, 2, 3
CAC	35dB
Availability	Stock
Size	Nominal 1200 x 600mm Actual 1191 x 591mm
Pallet Size	200 Tiles

PRODUCT	PERFORATED PANEL
Thickness	13mm
Surface Finish visible	Vinyl laminate
Surface Finish back	Paper
Core	Plaster
Edge Profile	Square
Edge Finish	Short edges paper wrapped, long edges machine cut
Grid	To suit an exposed grid
Accessibility	Easily demountable
Cleaning	Dust, vacuum or wipe with a damp cloth
Panel Mass (kg/m <sup>2</sup> )	10
Colour	White
EFHI	0, 0, 0, 4
NRC	0.49 with Bradford Anticon 55 (foil uppermost)
Availability	Stock
Size	Nominal 1200 x 600mm Actual 1191 x 591mm
Pallet Size	200 Tiles

### CSR Gyprock™ Warranty



Gyprock™ products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system. Gyprock™ continues to lead the market with premium quality products which are the preferred choice of plastering professionals. Gyprock™ plasterboard products are manufactured to the Australian Standards AS2588 providing confidence in quality of product and support. For details on our product warranty, please log onto [www.gyprock.com.au/warranty](http://www.gyprock.com.au/warranty), or contact us on 1300 306 556.

